



SPECIFICATION 2402-200:

1. MAT'LS: GLAND and HOUSINGS - 316L CRES, PISTON - 17-4 PH CRES
2. SWITCH RATING: 48VDC, 300 MA
3. INSULATION RESISTANCE: 20 MEGOHM MIN. AT 500VDC
4. PRESSURE RATING:
 - A. OPERATING: 1/8 NPT PORT - 0-3000 PSI
1/4 NPT PORT - 0-3000 PSID
 - B. PROOF PRESSURE - 4500 PSI EACH PORT
 - C. DESIGN BURST PRESSURE - 9000 PSI EACH PORT
 - D. SWITCH POINT: 1500+/- 100 PSID INCREASING PRESSURE
 - E. PRESSURE AT "H" MUST EXCEED PRESSURE AT "L"
 - F. USE OF PRESSURE SNUBBER IS REQUIRED AT PORT "H".

UNDERWATER CONNECTOR (2) →
MATES WITH RMA-FS/A-FLS-D (3H)

2402-200

DIMENSIONS
ARE INCHES.

HYDRACON COMPANY		
Anahem, CA		
SCALE: FULL	APPROVED BY: VAD 4-19-07	DRAWN BY
DATE: 3-9-07		REVISED 4-19-07
PRESSURE SWITCH - DIFFERENTIAL		
	REV.	DRAWING NUMBER 2402-200