



(CONNECTOR OMITTED)

PORT PER AND10050-4  
1/4" TUBE SIZE -3 PL.

**SPECIFICATION 1720-100:**

1. DESCRIPTION: SOLENOID OPERATED VALVE, 3-WAY, 2-POSITION, NORMALLY OPEN.
2. SYSTEM FLUID PRESSURES:  
OPERATING: 0 - 6,000 PSIG  
PROOF: 9,000 PSIG; BURST: 15,000 PSIG
3. FLOW: APPROX. 0.16 ESEOD
4. PORTS: AND10050-4 (1/4" TUBE SIZE)
5. INTERNAL LEAKAGE: ZERO (BUBBLE TIGHT)  
EXTERNAL LEAKAGE: ZERO (BUBBLE TIGHT)
6. ELECTRICAL: 17.6 AMPS AT 24 VDC.
7. SOLENOID CONSTRUCTION: STAINLESS STEELS
8. VALVE CONSTRUCTION: STAINLESS STEELS
9. WEIGHT: 3 LBS

DO NOT SCALE

<b>HYDRACON COMPANY, INC.</b> P.O. Box      Anaheim, CA		
SCALE: FULL	APPROVED BY:	DRAWN BY:
DATE: 4-'02		
SOLENOID VALVE, 3 WAY, 2 POS, N.O. 1/4" LINE SIZE, 24 VDC		
	REV.	DRAWING NUMBER 1720-100