



SPECIFICATIONS:

1. PRESSURE: OPERATING. 3,000 PSI
 PROOF. 4,500 PSI
 BURST. 7,500 PSI
2. LEAKAGE: BUBBLE TIGHT
3. PORTS: AND10050-4
4. MATERIALS: BODY ALUMINUM
 SPOOL AND SOLENOID, CRES STL
5. ELECTRICAL: VOLTAGE. 18-32 VDC
 COIL RESISTANCE. . . 19 OHMS @ 70° F
 PULL-IN. 18 VDC MAX @ 70° F
 DROP-OUT. 2 VDC MIN @ 70° F
6. FLOW $C_v = 0.2$ (ESEOD = 0.1)
7. WEIGHT: 1.6 LB. (CALC.)
8. SEATS AND SEALS FOR 350° F TO 400° F SERVICE.

HYDRACON COMPANY, INC.			
<small>PO BOX 27584 Anaheim, CA USA</small>			
SCALE: 1/1	APPROVED BY:	DRAWN BY:	
DATE: 6-20-94		REVISED: 8-13-94	
SOLENOID VALVE - 4-WAY, 2-POSITION, N.C., 24 VDC			
NEXT ASSY:	SHEET 1 OF 1	REV.	DRAWING NUMBER:
	DRAWING IN 2D	A	1705-300