



SPECIFICATIONS: 1720-100

1. DESCRIPTION: SOLENOID OPERATED VALVE,
3-WAY, 2-POSITION, NORMALLY OPEN.
2. SYSTEM FLUID PRESSURES:
OPERATING: 0 - 6,000 PSIG
PROOF: 9,000 PSIG
BURST: 15,000 PSIG
3. FLOW: APPROX. 0.16 ESEOD
4. PORTS: AND10050-4 (1/4" TUBE SIZE)
5. INTERNAL LEAKAGE: ZERO (BUBBLE TIGHT)
EXTERNAL LEAKAGE: ZERO (BUBBLE TIGHT)
6. ELECTRICAL: 17.6 AMPS AT 24 VDC.
7. SOLENOID CONSTRUCTION: STAINLESS STEELS
8. VALVE CONSTRUCTION: STAINLESS STEELS
9. WEIGHT: 3 LBS.

HYDRACON COMPANY, INC.

PO BOX 27584
Anaheim, CA USA

SCALE: NONE	APPROVED BY:	DRAWN BY:
DATE: 4-2002		REVISED:
SOLENOID VALVE, 3-WAY, 2-POSITION, N.O., 1/4" LINE SIZE, 24 VDC		
NEXT ASSY:	SHEET 1 OF 1 DRAWING IN 2D	REV. DRAWING NUMBER: 1720-100