



SPECIFICATION: 2407-100

1. ELECTRIC SWITCH
 ELECTRICAL RATING: 5 AMPS, 250V AC
 SWITCH: SPDT, N.O. AND N.C.
 INSULATION RESISTANCE: 20 MEGOHM MIN. AT 500VDC
 NO EXTERNAL POWER REQUIRED.
2. PRESSURE RATING:
 OPERATING: 1/4" PORT - 0-6,000 PSID
 AMBIENT: 1 ATM
 DESIGN PROOF: 9,000 PSI AT PORT
 SWITCH POINT: TO 6,000 PSI MAX. INCREASING PRESSURE
 USE OF PRESSURE SNUBBER IS RECOMMENDED.
3. MATERIALS: HOUSING - 316L CRES
 PISTON - 17-4 PH CRES
 SEAL - VITON
4. NOT SUBMERSIBLE

HYDRACON COMPANY, INC.			
<small>PO BOX 27584 Anheim, CA USA</small>			
SCALE: FULL	APPROVED BY:		DRAWN BY:
DATE: 12-10-07			REVISED:
PRESSURE SWITCH - 6,000 PSI			
NEXT ASSY:	SHEET 1 OF 1	REV.	DRAWING NUMBER:
	DRAWING IN 2D		2407-100