



HYDRACON SUBSEA

DIVER-OPERATED PUSH-BUTTON SWITCH

Features:

- OCEAN SUBMERSIBLE
- PANEL MOUNT STYLE
- INSENSITIVITY TO SEA PRESSURE
- LOW HYSTERESIS
- MAGNETICALLY COUPLED

More features:

- Shrouded push button
- No internal frictional parts
- This is a two-wire system
- No transmitter is needed
- Zero power consumption

Specifications:

1. Contact rating: 50W switching capability, up to 500V.
3. Contact Life: 1 x 10⁶ Ops. @ 50V, 1.0A
200 x 10⁶ Ops. @ 1.0V, 10mA
4. Vibration Res.: 20g @ 10 Hz – 500 Hz
5. Shock Res.: 50g @ 11 ms, ½ sine wave
6. Wet side to 1,000 psi ambient sea pressure
7. Dry side 1ATM
8. Materials: 316L stainless steel
9. Size: 1.38" dia x 0.60" height + Mounting thread
10. Mounting thread ¾"-16 thread x 0.9" long
11. Face seal panel mounting style with 6" long lead wires
12. Weight: 4.6 oz



Model 1821-101

Providing high reliability and long life, this hermetically sealed panel mount switch is similar to 1809-200.

First customer's response: "...a thing of beauty, very nice finish & operation".

www.hydracon.com

NPA1821-101A

Hydracon Company, Inc., P.O. Box 27584, Anaheim, CA 92809, U.S.A. Tel: 714-281-2460 Fax: 714-281-1199
web page: www.hydracon.com email: hydracon@hydracon.com