



SPECIFICATION: 2800-100

1. TYPE: PRESSURE ACTUATED VALVE,
NORMALLY CLOSED, 2-WAY, 2-POS.
2. PRESSURE CHARACTERISTICS:
OPERATING: 3,000 PSI
PROOF: 4,500 PSI
ACTUATION: 1,300 PSI
(INCREASING PRESSURE)
3. FLOW: 0.10" MIN ESEOD
4. LEAKAGE: BUBBLE TIGHT
5. MATERIALS OF CONSTRUCTION:
ALL MACHINED PARTS ARE VARIOUS GRADES OF
STAINLESS STEEL
SPRING MUSIC WIRE
NPT PLUG BRASS
O-RING BUNAN AND ETHYLENE PROPYLENE
6. NOTE: NOT INTENDED FOR SEA WATER SERVICE.

HYDRACON COMPANY, INC.

PO BOX 27584
Anaheim, CA USA

SCALE: FULL	APPROVED BY:	DRAWN BY:
DATE: 8-8-97		REVISED:
PRESSURE OPERATED VALVE, 2-WAY, 1300 PSI ACTUATION		
NEXT ASSY:	SHEET 1 OF 1 DRAWING IN 2D	REV. DRAWING NUMBER: 2800-100