



SPECIFICATION, 1700-100:

1. SOLENOID VALVE, SUBMERSIBLE, LATCHING WITH MANUAL, UNLATCH, 2-WAY, NORMALLY CLOSED.
2. PRESSURE, OPERATING: 3000 PSIG
PROOF: 4500 PSIG
BURST: 7500 PSIG
3. PORTS PER MS 33649-4.
4. MATERIAL: METALS ARE ALL STAINLESS STEELS.
SEALS ARE AS REQUIRED FOR FLUID COMPATIBILITY.
5. SOLENOID: HERMETICALLY SEALED, STAINLESS STEEL.
6. ELECTRICAL: 1.0 AMP @ 24 VDC.
7. FLUID MEDIA: CORROSIVE LIQUIDS AND GAS.
8. LEAKAGE: INTERNAL & EXTERNAL: BUBBLE TIGHT.
9. CONTAMINATION TOLERANT 40 TO 100 MICRON.

HYDRACON COMPANY, INC.

PO BOX 27584
Anaheim, CA USA

SCALE: 1/1	APPROVED BY: VAP	DRAWN BY:
DATE: 9/93		REVISED:
SOLENOID VALVE - SUBMERSIBLE, LATCHING, N.C., 2-WAY, 1/4"		
NEXT ASSY:	SHEET 1 OF 2	REV.
	DRAWING IN 2D	DRAWING NUMBER: 1700-100