



SPECIFICATION, 1708-200

1. TYPE: SOLENOID ACTUATED VALVE, COAXIAL, NORMALLY CLOSED, 2-WAY, 2-POS. PRESSURE BALANCED POPPET, WITH CARTRIDGE SEAL REPLACEMENT FEATURE.
2. OPERATING PRESSURE: 5,000 PSI
3. FLUID MEDIA: STREAM TO 400 F
4. FLOW:  $C_v = .044$  (0.6 GPM @ 200 PSID)
5. LEAKAGE: BUBBLE TIGHT, INTERNAL & EXTERNAL
6. ELECTRICAL: 1 AMP @ 28 VDC
7. MATERIALS IN CONTACT WITH FLUID ARE CORROSION RESISTANT STEELS
8. WEIGHT: 14 OZ.
9. NOTE: THIS IS NOT A SUBMERSIBLE MODEL.

**HYDRACON COMPANY, INC.**

PO BOX 27584  
Anaheim, CA USA

SCALE: FULL	APPROVED BY:	DRAWN BY:
DATE: 6-9-99		REVISED:
SOLENOID VALVE - COAX TYPE, 1/8" LINE SIZE, STREAM SERVICE		
NEXT ASSY:	SHEET 1 OF 1 DRAWING IN 2D	REV. DRAWING NUMBER: 1708-200