



UNDERWATER CONNECTOR (2)
MATES WITH RMA-FS/A-FLS-D (3H)

SPECIFICATION: 2402-200

1. MATERIALS: GLAND AND HOUSINGS - 316L CRES, PISTON - 17-4 PH CRES
2. SWITCH RATING: 48VDC, 300 MA
3. INSULATION RESISTANCE: 20 MEGOHM MIN. AT 500VDC
4. PRESSURE RATING:
 - A. OPERATING: 1/8 NPT PORT - 0-3,000 PSI
1/4 NPT PORT - 0-3,000 PSID
 - B. PROOF PRESSURE - 4,500 PSI EACH PORT
 - C. DESIGN BURST PRESSURE - 9,000 PSI EACH PORT
 - D. SWITCH POINT: 1,500 +/-100 PSID INCREASING PRESSURE
 - E. PRESSURE AT "H" MUST EXCEED PRESSURE AT "L"
 - F. USE OF PRESSURE SNUBBER IS REQUIRED AT PORT "H".

HYDRACON COMPANY, INC.

PO BOX 27584
Anahelm, CA USA

SCALE: FULL	APPROVED BY: VAP 4-19-07	DRAWN BY:
DATE: 3-9-07		REVISED: 4-19-07

PRESSURE SWITCH - DIFFERENTIAL

DIMENSIONS ARE IN INCHES.	SHEET 1 OF 1	REV.	DRAWING NUMBER: 2402-200
	DRAWING IN 2D		