



HYDRACON SUBSEA

SUBSEA SOLENOID VALVE

Oil Spill Containment System

Features:

- FULL FLOW - 1/2" NPT
- DIRECT SOLENOID OPERATED
- BUBBLE-TIGHT CLOSURE
- CONTAMINATION TOLERANT
- SEAWATER SUBMERSIBLE
- UNDERWATER CONNECTOR
- HERMETICALLY SEALED SOLENOID
- SHOCK RESISTANT
- LONG CYCLE LIFE
- LOW POWER CONSUMPTION
- **NO ADJUSTMENTS NEEDED**

Specification:

1. 2-way, 2-position, normally closed
2. Ocean Submersible
3. Fluid Pressure: 3,000 psid Operating
4. Ocean Ambient to 4,500 psi
5. Fluids: hydraulic or pneumatic
6. Ports: 1/2" NPTF
7. Zero Leakage
8. Electrical: 1.85 amps @ 24vdc
9. Corrosion Resistant Stainless Steels
10. Weight: <15 lbs.
11. Size: 3.25" sq x 8"+ subsea connector



**MODEL NO.
1723-100**

Submersible solenoids meet IPX8 of IEC 529 for protection against the effects of continuous water submersion.

PROVEN PERFORMANCE - "the subsea specialist" Since 1969

MANUFACTURER: CUSTOM SUBSEA SWITCHES, SOLENOIDS, AND SOLENOID VALVES

www.hydracon.com

NPA1723-100C.doc

Hydracon Company, Inc., P.O. Box 27584, Anaheim, CA 92809, U.S.A. Tel: 714-281-2460 Fax: 714-281-1199
e-mail: hydracon@hydracon.com